

## simex *cuff S* automated subglottic aspiration system



<b>Item No.</b>	<b>100679-3</b>	
<b>Flow rate</b>	<b>max. 8 l/min</b>	
<b>Pressure</b>	<b>-60 mbar to -300 mbar (in steps of 10 mbar)</b>	
<b>Containers</b>	<b>Disposable secretion container system, 1000 ml</b>	
<b>Nominal mains voltage (mains-powered)</b>	<b>100 – 240V AC primary / 12V DC secondary</b>	
<b>Maximum current</b>	<b>1.25 A</b>	
<b>Mains frequency (mains-powered)</b>	<b>50 / 60 Hz</b>	
<b>Rating</b>	<b>15 W (charging and operation) 10 W (charging only)</b>	
<b>Current drawn</b>	<b>1.25 A at 12 V</b>	
<b>Rechargeable battery</b>	<b>7.4 V, 4.4 Ah – lithium ion</b>	
<b>Dimensions (H x W x D)</b>	<b>290 x 259 + 100 (container) x 130 mm</b>	
<b>Weight (basic device)</b>	<b>Approx. 2.2 kg</b>	
<b>Operating mode</b>	<b>Intermittent Aspiration</b>	
<b>Running time</b>	<b>Mains</b>	<b>continuous operation</b>
	<b>Battery</b>	<b>approx. 18 hours (device at full capacity)</b>
<b>Noise emission</b>	<b>35 dB (A)</b>	
<b>Degree of protection acc. IEC 60601-1</b>	<b>Type BF</b>	
<b>Protection class acc. IEC 60601-1</b>	<b>II</b>	
<b>CE mark</b>	<b>CE0843</b>	